

EMERGENCY UNITS



EMERGENCY 2600 ON WALL

IP42 / IP65

Power consumption: 2W

White polycarbonate / Opal polycarbonate diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator on request

H79mm; A136mm; L365mm

D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (cd)	D/M	UD/NM	IP	
EM2601	3.6/1	1	25	•	-	IP42	€ 108,85
EM2602	3.6/1	1	25	-	•	IP42	€ 103,75
EM2603	3.6/1.5	3	25	•	-	IP42	€ 124,50
EM2604	3.6/1.5	3	25	-	•	IP42	€ 119,30
EM2601IP	3.6/1	1	25	•	-	IP65	€ 119,75
EM2602IP	3.6/1	1	25	-	•	IP65	€ 114,25
EM2603IP	3.6/1.5	3	25	•	-	IP65	€ 136,40
EM2604IP	3.6/1.5	3	25	-	•	IP65	€ 130,85



EMERGENCY 2900 CEILING RECESSED

Power consumption: 1,2W

Sheet steel body grey

Plexiglass diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator

Test pushbutton

Emergency labels - all 4 types are standardly included in the package

D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (lm)	D/M	UD/NM	IP	
EM2901	3.6/1	1	20	-	•	IP20	€ 128,55
EM2903	3.6/1.5	3	20	-	•	IP20	€ 130,90
EM2904	3.6/1	1	20	•	-	IP20	€ 152,55
EM2906	3.6/1.5	3	20	•	-	IP20	€ 154,90



EMERGENCY 2910 CEILING SURFACED

Power consumption: 1,2W

Sheet steel body grey

Plexiglass diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator

Test pushbutton

Emergency labels - all 4 types are standardly included in the package

D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (lm)	D/M	UD/NM	IP	
EM2911	3.6/1	1	30	-	•	IP20	€ 165,85
EM2913	3.6/1.5	3	30	-	•	IP20	€ 175,15
EM2914	3.6/1	1	30	•	-	IP20	€ 172,95
EM2916	3.6/1.5	3	30	•	-	IP20	€ 182,45