


**EMERGENCY 3100 / IP65**


Housing: polycarbonate + ABS
 Polycarbonate diffuser
 Duration 1h on request
 Warranty: 3 years

EM3102	2W / 115-245 lm / 3h	
EM3104	5W / 223-475 lm / 3h	
EM3106AT	2W / 115-245 lm / 3h	
EM3108AT	5W / 223-475 lm / 3h	

**EMERGENCY 3110 / IP65**


Housing: polycarbonate + ABS
 Polycarbonate diffuser
 Duration 1h on request
 Warranty: 3 years

EM3112	2W / 104-222 lm / 3h	
EM3114	5W / 196-418 lm / 3h	
EM3116AT	2W / 104-222 lm / 3h	
EM3118AT	5W / 196-418 lm / 3h	

**EMERGENCY 3220 / IP20**

Housing: polycarbonate
 Duration 1h on request
 Warranty: 3 years

EM3222	2,5W / 242 lm / 3h	
EM3223	4,5W / 330 lm / 3h	
EM3225AT	2,5W / 242 lm / 3h	
EM3226AT	4,5W / 330 lm / 3h	



EMERGENCY 2600 ON WALL

IP42 / IP65

Power consumption: 2W

White polycarbonate / Opal polycarbonate diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator on request

H79mm; A136mm; L365mm



D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (cd)	D/M	UD/NM	IP	
EM2601	3.6/1	1	25	•	-	IP42	
EM2602	3.6/1	1	25	-	•	IP42	
EM2603	3.6/1.5	3	25	•	-	IP42	
EM2604	3.6/1.5	3	25	-	•	IP42	
EM2601IP	3.6/1	1	25	•	-	IP65	
EM2602IP	3.6/1	1	25	-	•	IP65	
EM2603IP	3.6/1.5	3	25	•	-	IP65	
EM2604IP	3.6/1.5	3	25	-	•	IP65	

EMERGENCY 2900 CEILING RECESSED

Power consumption: 1,2W

Sheet steel body grey

Plexiglass diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator

Test pushbutton

Emergency labels - all 4 types are standardly included in the package



D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (lm)	D/M	UD/NM	IP	
EM2901	3.6/1	1	20	-	•	IP20	
EM2903	3.6/1.5	3	20	-	•	IP20	
EM2904	3.6/1	1	20	•	-	IP20	
EM2906	3.6/1.5	3	20	•	-	IP20	

EMERGENCY 2910 CEILING SURFACED

Power consumption: 1,2W

Sheet steel body grey

Plexiglass diffuser

Ni-Cd battery

Protection of battery against overload and discharge

LED charging indicator

Test pushbutton

Emergency labels - all 4 types are standardly included in the package



D/M: permanent

UD/NM: not permanent

code	battery NI-CD (V/Ah)	duration (h)	light output (lm)	D/M	UD/NM	IP	
EM2911	3.6/1	1	30	-	•	IP20	
EM2913	3.6/1.5	3	30	-	•	IP20	
EM2914	3.6/1	1	30	•	-	IP20	
EM2916	3.6/1.5	3	30	•	-	IP20	