

Product data sheet





SQUARE

12,5W – 25W 1400lm – 3000lm 2700K – 4000K 15° - 45°



Description	ceiling mounted fixture
Dimensions (mm)	73mm x 73mm x 95mm
Weight (kg)	72 g
Housing	Housing: die cast alu
Colour	White, black, grey, copper, gold, graphite,...
Optical system	Reflector
Lighting Distribution	Direct 15° - 45° - symmetrical
Unified Glare Ratio	<22
Colour temperature (K)	2700K – 4000K
CRI (Ra)	90
SCDM	2
Net lumen output (25°C)	1400lm – 3000lm
Efficacy – LOR (lm/W)	112 lm/W – 125lm/W
Power (driver incl.)	12,5W – 25W
Driver	Driver incorporated Non dim
IP	IP 20
IK	IK 02
Lifetime (hours)	50.000 hours L80 B20
Warranty	5 years
Origin	Spain
Norms	LVD 2006/95/EC EMC 2004/108/EC RoHS 2001/65/EC



All specifications, descriptions and images are purely informative, not binding and subject to errors and changes

Euro-Luce Light Engineering
Ballingsweg 25 – 9620 Zottegem
info@euro-luce.be
www.euro-luce.be
Tel 0032 54 55 71 10

Marks

